

**PART NUMBER: 51-1203C**

**SPECIFICATION SHEET**

<b>DESCRIPTION</b>	12 AWG 3 Conductor, Bare Copper, Plenum Shielded, UL Listed (UL) CL3P
<b>CONDUCTOR</b>	12AWG (19 Strand) Bare Copper
<b>INSULATION</b>	Plenum Rated Polyvinylchloride, 0.009"
<b>COLOR CODE</b>	Black, White, Red
<b>SHIELD</b>	Aluminum Mylar Tape – 100% Coverage
<b>DRAIN WIRE</b>	24 AWG 7 Strand Tinned Copper
<b>JACKET</b>	Plenum Rated Polyvinylchloride, 0.015"
<b>JACKET COLOR</b>	Natural
<b>OVERALL DIAMETER</b>	0.266"
<b>WEIGHT</b>	82 Lbs/Mft
<b>PRINT LEGEND</b>	ONSITE WIRE & CABLE (866) 960-1059 P/N 51-1203C 12AWG 3C (UL) CL3P OR (UL) FPLP 75°C "ROHS" FT-6
<b>RATINGS</b>	0°C to 75°C   300V

**ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION**

