

**PART NUMBER: 51-1604C**

**SPECIFICATION SHEET**

|                         |   |
|-------------------------|---|
| <b>DESCRIPTION</b>      | 16 AWG 4 Conductor, Bare Copper, Plenum Shielded, UL Listed (UL) CMP C                                  |
| <b>CONDUCTOR</b>        | 16AWG (19 Strand) Bare Copper   |
| <b>INSULATION</b>       | Plenum Rated Polyvinylchloride, 0.007"  |
| <b>COLOR CODE</b>       | Black, Red, White, Green  |
| <b>SHIELD</b>           | Aluminum Mylar Tape – 100% Coverage   |
| <b>DRAIN WIRE</b>       | 24AWG 7 Strand Tinned Copper  |
| <b>JACKET</b>           | Plenum Rated Polyvinylchloride, 0.015"  |
| <b>JACKET COLOR</b>     | Natural   |
| <b>OVERALL DIAMETER</b> | 0.206"  |
| <b>WEIGHT</b>           | 48 Lbs/Mft  |
| <b>PRINT LEGEND</b>     | ONSITE WIRE & CABLE (866) 960-1059 P/N 51-1604C 16AWG 4C (UL) CMP C(UL)US OR (UL) CL3P 75°C FT-6 "ROHS" |
| <b>RATINGS</b>          | 0°C to 75°C   300V  |

**ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION**

