

**PART NUMBER: 61-1204C**

**SPECIFICATION SHEET**

<b>DESCRIPTION</b>	12 AWG 4 Conductor, Bare Copper, Non-Plenum Shielded, UL Listed (UL) CL3R
<b>CONDUCTOR</b>	12AWG (19 Strands) Bare Copper
<b>INSULATION</b>	Polyvinylchloride, 0.010"
<b>COLOR CODE</b>	Black, White, Red, Green
<b>SHIELD</b>	Aluminum/Mylar – 100% Coverage
<b>DRAIN WIRE</b>	24AWG 7 Strand Tinned Copper
<b>JACKET</b>	Polyvinylchloride, 0.015"
<b>JACKET COLOR</b>	Gray
<b>OVERALL DIAMETER</b>	0.297"
<b>WEIGHT</b>	106 Lbs/Mft
<b>PRINT LEGEND</b>	ONSITE WIRE & CABLE (866) 960-1059 P/N 61-1204C 12AWG 4C (UL) FPLR OR (UL) CL3R 75°C SUN RES "ROHS" FT-4
<b>RATINGS</b>	0°C to 75°C   300V

**ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION**

