

**PART NUMBER: 51-2201P-ARC156-GN**

**SPECIFICATION SHEET**

<b>DESCRIPTION</b>	22 AWG 1 Pair, Tinned Copper, Shielded RS-485, RS422, RS232 Low Cap Plenum Rated, UL Listed C(UL)US CL3P
<b>CONDUCTOR</b>	22 AWG (7 Strands) Tinned Copper
<b>INSULATION</b>	Plenum Rated Foamed FEP, 0.018"
<b>COLOR CODE</b>	Black, White
<b>SHIELD</b>	Aluminum Mylar Tape – 100% Coverage
<b>DRAIN WIRE</b>	24 AWG 7 Strand Tinned Copper
<b>JACKET</b>	Plenum Rated PVC, 0.015"
<b>JACKET COLOR</b>	Green
<b>OVERALL DIAMETER</b>	0.161"
<b>WEIGHT</b>	16 Lbs/Mft
<b>PRINT LEGEND</b>	ONSITE WIRE & CABLE (866) 960-1059 P/N 51-2201P-ARC156-GN 22AWG 2C (UL) CMP C(UL)US or (UL) CL3P 75°C FT-6 "ROHS"
<b>CAPACITANCE</b>	12.5 pF/Ft Nom.
<b>IMPEDANCE</b>	100 OHMS Nom.
<b>RATINGS</b>	0°C to 75°C   300V

**ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION**

