

**PART NUMBER: 71-1402C-STR**

**SPECIFICATION SHEET**

<b>DESCRIPTION</b>	14 AWG 2 Conductor, Stranded Bare Copper, Plenum Rated, Shielded, UL Listed (UL) FPLP
<b>CONDUCTOR</b>	14AWG (7 Strands) Bare Copper
<b>INSULATION</b>	Plenum Rated Polyvinylchloride, 0.009"
<b>COLOR CODE</b>	Black, Red
<b>SHIELD</b>	Aluminum Mylar – 100% Coverage
<b>DRAIN WIRE</b>	24AWG 7 Strand Tinned Copper
<b>JACKET</b>	Plenum Rated Polyvinylchloride, 0.015"
<b>JACKET COLOR</b>	Red
<b>OVERALL DIAMETER</b>	0.214"
<b>WEIGHT</b>	41 Lbs/Mft
<b>PRINT LEGEND</b>	ONSITE WIRE & CABLE (866) 960-1059 P/N 71-1402C-STR 14AWG 2C (UL) FPLP OR (UL) CL3P C(UL)US 75°C FT-6 "ROHS"
<b>RATINGS</b>	0°C to 75°C   300V

**ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION**

